

MICOM-2RS *Front Mount*

**Ruggedized HF-SSB ALE Mobile/Fixed
Digital Signal Processing Radio
125watt PEP/Average 1.6-30 MHz**



Micom-2RS is an advanced Ruggedized Digital Signal Processing transceiver, intended for very wide area radio communications. It provides, Voice, Data, Fax and E-mail solutions with a high degree of sophistication, signal quality and reliability, while being very simple to operate.

MICOM-2RS with its compact size provides maximum ease of installation. The Automatic Link Establishment-ALE (per FED-STD 1045 and MIL-STD 188/141B) is a Standard Feature.

Features

- Enhanced DSP based Radio Platform
- Enhanced features for better communication
- Ruggedized Mobile / Fixed Transceiver
- Front panel programming
- Advanced digital technology
- Conforms to MIL-STD 810 and EIA Specifications
- ALE per FED-STD-1045 and MIL-STD-188/141B
- High MTBF
- Security access code
- Variable Bandwidth for optimal signal processing
- Voice activated digital squelch
- Programmable channel scan
- Digital noise blanking and clarifier
- Guard and Priority Channels
- Continuous duty operation (optional)
- Multi-language Liquid Crystal Display
- BITE (Built-in Test)
- Meets FCC and EMC standards
- Selectable front-end Attenuator
- Enhanced Voice Quality
- Excellent frequency stability
- Selectable Power Output
- Small Size, Light Weight
- Variable notch filter
- Sub-octave pre-selector
- Military type audio connectors
- Military type accessories
- Adaptable internal configuration options
- Multinet Operation for A.L.E (optional)

MICOM-2RS Front Mount



Ruggedized HF-SSB ALE Mobile/Fixed Digital Signal Processing Radio 125watt PEP/Average 1.6-30 MHz

GENERAL					
Model Number: M85AMN0KV5-K					
Frequency Range: 1.6 MHz Tx, 100 KHz-30 MHz Rx					
Number of Channels: 200					
Scanning: 5 groups with up to 100 channels per group					
Frequency Stability: 0.6 PPM, (0.1 PPM optional)					
Frequency Drift (Aging): 1 PPM per year					
Synthesizer Lock Time: 10 msec max.					
Frequency Resolution: 10 Hz					
Audio Bandwidths @ -6dB: Voice: 350 to 2700 Hz					
CW: 650 to 1150 Hz					
Low speed data: 1450 to 1950 Hz					
High speed data*: 350 to 3300 Hz					
Operating Temp. Range: -30° to +60°C					
Humidity: -95% @ 50°C					
Operating Voltage: 13.8 VDC ±20% Neg. Ground					
ALE: Per FED-STD 1045 and Mil-STD 188/141A					
Current Drain	Receive		Transmit		
	Squelched	Full Audio	Voice	2 Tone	1 Tone
@ 13.8 VDC	2.2A	3A	14A	23A	28A
@ 26.4 VDC	1.3A	1.8A	8A	13A	16A
Dimensions and Weight	Height	Width	Depth	Weight	
	mm/inch	mm/inch	mm/inch	Kg	Lb
	92 / 3.7	302 / 11.9	285 / 11.3	5.9	13

* Optional, for authorized users only

RECEIVER
Sensitivity (SINAD) SSB: 0.5µv for 10 dB SINAD (Voice) (0.3µv Typically)
0.1-1.6 MHz - reduced performance
1/2 Rated Power Sensitivity: 1µv for 2.5W audio @ speaker
Selectivity: -6 dB @ 350 to 2700 Hz
-60 dB @ -1 kHz, +4 kHz
Image Rejection: -80 dB
IF Rejection: -85 dB
Undesired Sideband Rejection: -55 dB @ -1 kHz
Spurious Rejection: -80 dB
Intermediation Rejection: -80 dB
Cross Modulation Rejection: -100 dB @ 100 kHz
Desensitization: -100 dB @ 100 kHz
Reciprocal Mixing: -100 dB @ 100 kHz
Audio Power @ Speaker: 5W @ 2.5% distortion
RGC Range: 5µV/1V (2 dB change in output level)
RGC Time Constant Voice: Attack time 10 msec
Release time 1500 msec
Data: Attack time 10 msec
Release time 10 msec
Squelch: Constant SINAD (digital)
Clarifier Range: ±200 Hz in 10 Hz steps
Receiver Tuning Adjustments: None
Preselector Sections: Sub-octave (1.6 MHz to 30 MHz range)
Antenna Input Protection: 20 kV maximum transient, 100V RMS for 2 minutes

TRANSMITTER	
Output Power:	125w P.E.P. and average
Reduced Power Levels:	25W, 62W 100W (RSS Programmable)
Audio Bandwidth Ripple:	3 dB
Intermodulation:	-31 dB/P.E.P. (-35 dB/P.E.P. Typical Note 1)
Harmonic Emissions:	-64 dB/P.E.P. (-70 dB/P.E.P. Typical Note 1)
Spurious Emissions:	-64 dB/P.E.P. (-70 dB/P.E.P. Typical Note 1)
Carrier Suppression:	-50 dB/P.E.P.
Undesired Sideband Suppression:	-55 dB/P.E.P.
Audio-Distortion:	2.5%
1/2 Power Mic. Sensitivity:	25 to 125 mV (RMS)/600 ohms
Hum & Ripple:	<50 dB
Inband Noise:	-60 dB (30 Hz BW)
Tx/Rx Switching Time:	10 msec
Tx Tuning Adjustments:	None

Note 1: Values noted as typical are valid over 90% or more of the frequency range.

MILITARY & INDUSTRIAL STANDARDS			
Micom-2RS meets the following US military and industrial standard requirements for adverse environmental conditions (without the need external shock mounts)			
Environmental Condition	US Military STD 810C	US Military STD 810D	US Military STD 810E
Vibration	Method 514.2	Method 514.3	Method 514.4
Shock	516.2	516.3	516.4
Rain	506.1	506.2	506.3
Dust	510.1	510.2	510.3
Salt Fog	509.1	509.2	509.3
The Micom-2RS also meets the EIA-RS152B for shock, vibration and applicable test procedures, US FCC for channel occupancy, spurious, interference and frequency tolerance. It is manufactured according to the demanding standards ISO 9001 and EMC (Electromagnetic Compatibility).			
FCC information; Emissions: J3E, R3E, H3E, J2A, J2B			
FCC Applicable Parts of Rules: 15, 80, 90			
FCC Type Acceptance Number : ABZ9QCC1635			
With High Stability Option: ABZ9QCC1634			

OPTIONS	
● RS232 Remote Contol Interface	● Micom-Link Interface
● Linear Amplifier Interface	● 24 VDC Operation
● Phone Patch Interface	● Rss for PC (Radio and ALE)
● Data/Fax Modem Interface	● High (0.1 PPM) Frequency stability
	● Multinet Operation (for A.L.E)

MAJOR ACCESSORIES	
● Phone Patch	● Encryption Voice/Data
● Micom-Link (FM-HF repeater)	● AC Power Supply
● Automatic Antenna Tuner	● 1 kW Amplifier
● Continuous Duty Kit	● Antennas and Grounding kit
● Military Audio Accessories	● Data/Fax Modem
● Automatic Telephone Interconnect	● CW Key & Headphones



Mobot USA
 1721 West Paul Dirac Dr.
 Tallahassee, Florida 32310
 Tel: 850 580 0420 · Fax: 850 580 2626
 marketing@mobotusa.com · www.mobot.com

Mobot
 A Tadiran Communications Division
 3 Israeli Shimon St., P.O.B 5090, Rishon LeZion 75151 Israel
 Tel: 972 3 9518050 · Fax: 972 3 9527233
 marketing@mobot.com · www.mobot.com